



POPLON CHEMIE

Manufacturers of: **LEATHER CHEMICALS & TEXTILE AUXILIARIES**

An ISO 9001-2015 Certified Company

I/S Nijjarpura Village, G.T. Road
Amritsar-143001 INDIA
www.poplonchemie.com
chemie.poplon@gmail.com
sunilbehal@poplonchemie.com

Cell : +91 9815003892
Telefax : +91 183 2440892

POPTAN P540 RESIN TANNING AGENT

POPTAN P540 is used in the chrome tannage and in the production of chrome retans to improve the fullness, tightness of grain and light fastness.

- Appearance : Colourless slightly viscous liquid
- Chemical Nature : Anionic synthetic resin tanning agent based on acrylic polymers
- Active Matter : 37% (± 1)
- pH of 10% solution: 4.0-4.5
- Solubility : Readily soluble in water

PROPERTIES:

POPTAN P540 imparts improved fullness especially to the loosely structured parts like flanks, belly and shoulder.

POPTAN P540 imparts tightness of the grain and a very fine grain pattern is achieved. It also improves the light fastness of the leather.

continue2.....



POPLON CHEMIE

Manufacturers of: LEATHER CHEMICALS & TEXTILE AUXILIARIES

An ISO 9001-2015 Certified Company

I/S Nijjarpura Village, G.T. Road
Amritsar-143001 INDIA
www.poplonchemie.com
chemie.poplon@gmail.com
sunilbehal@poplonchemie.com

Cell : +91 9815003892
Telefax : +91 183 2440892

.....2.....

POPTAN P540 begins about a more intensive exhaustion of the chrome from the tan bath and an improved fixation, so that the usual amount of chrome employed may be reduced by 10-20%.

APPLICATION:

POPTAN P540 is particularly suitable for use as an auxiliary in the chrome tannage and retannage of chrome leathers to impart fullness and tightness of grain to the flat and loose parts of the skins and to improve the light fastness and fineness of the grain. A dosage of 2-3% recommended.

STORAGE:

POPTAN P540 has a shelf life of 1 year if it is stored in its tightly sealed original packaging at temperature of less than 40° c.